



! IMPORTANT NOTE !

1. ALL SHEARWALLS, WHICH ARE THE SHORT ENDWALLS UNDER LEAN-TO'S, PARTITION WALL, AND BI-FOLD DOOR ENDWALL IS SHEATHED W/ 7/16" APA RATED SHEATHING FASTENED TO 24" O.C. GIRTS W/ 8d NAILS, 3" O.C. PANEL PERIMETERS & 12" O.C. IN FIELD. PANELS ARE EXTENDED TO TRUSS/RAFTER TOP CHORDS.

2. AT CRITICAL LOCATION ADS-5'S MUST TAKE THE PLACE OF ADS-3. THESE LOCATIONS ARE MARKED WITH A ADS-5 NOTE OR SYMBOL (ADS-5). ADS-5 MUST BE ANCHORED TO CONCRETE WITH A 3/4" X 10" RAWLS POWER STUD IMBEDDED 7" INTO CONCRETE FOUNDATION. THERE ARE 12 LOCATIONS THAT THE ADS-5'S NEED TO BE PUT INTO PLACE.

A6 FLOOR PLAN
SCALE: 1/8"=1'

DATE: 11-18-98	SHEET	76772	06
JOB NUMBER	76772		
DRWN BY: MIKE KIEFFER	CHKD BY:	REV NO:	
JOB DESCRIPTION:	68X80X8 W/PORCH		
	2556 COUNTY ROAD, 253		
	KINGDOM CITY, MO 65282		
CUSTOMER:	SHRYOCK FARMS		
	2556 COUNTY ROAD, 253		
	KINGDOM CITY, MO 65282		
DEALER:	HLW BUILDERS		
	1312 BUS HWY#54 SOUTH		
	FULTON, MO 65251		
LESTER PRAIRIE, MINNESOTA	CUSTOMER SERVICE	320 - 395 - 2531	
BUILDINGS	A Product of	BUTLER MFG COMPANY	

THIS CERTIFICATION IS LIMITED TO THE STRUCTURAL DESIGN OF THE FRAMING AND COVERING PARTS MANUFACTURED BY LESTER BUILDING SYSTEMS (BUTLER MFG CO). ALL OTHER ITEMS SUCH AS EQUIPMENT, VENTILATION, PLUMBING, ELECTRICAL, ERECTION, DOORS, FIRE RESISTIVE REQUIREMENTS, INSPECTION, CONCRETE FLOORS, ETC. IS THE RESPONSIBILITY OF OTHERS.